

DIRAX

Pipe ø DN	Outside Pipe ø mils	Sleeve length		Leading edge length		Patch width		Epoxy primer kit S1239-Primer-Kit-252 or S1301-Primer-15-Kit			
		mm	in	mm	in	mm	in	W = 34 inches	W = 24 inches	W = 17 inches	W = 12 inches
80	3 500	400	15.75	390	15.375	100	4	1	1	1	1
100	4 500	460	18.0	465	18.3125	100	4	1	1	1	1
125	5 563	550	21.5	535	21.0625	100	4	1	1	1	1
150	6 625	640	25.0	670	26.375	100	4	1	1	1	1
200	8 625	800	31.5	795	31.3125	150	6	1	1	1	1
250	10 750	980	38.5	965	38	150	6	1	1	1	1
300	12 750	1150	45.5	1135	44.6875	150	6	1	1	1	1
350	14 000	1260	49.5	1235	48.625	150	6	1	1	1	1
400	16 000	1420	56.0	1390	54.75	150	6	1	1	1	1
450	18 000	1590	62.5	1565	61.625	150	6	1	1	1	1
500	20 000	1770	69.5	1750	68.9375	150	6	2	1	1	1
550	22 000	1950	77.0	1920	75.625	150	6	2	1	1	1
600	24 000	2110	83.0	2070	81.5	150	6	2	2	1	1
650	26 000	2270	89.5	2240	88.1875	150	6	2	2	1	1
700	28 000	2430	95.5	2390	94.0625	150	6	2	2	1	1
750	30 000	2600	102.5	2535	99.8125	150	6	2	2	1	1
800	32 000	2760	108.5	2705	106.5	150	6	2	2	1	1
850	34 000	2930	115.5	2855	112.375	150	6	2	2	1	1
900	36 000	3100	122.0	3000	118.125	150	6	2	2	1	1
1000	40 000	3430	135.0	3310	130.3125	150	6	2	3	2	1
1050	42 000	3590	141.5	3520	138.5625	150	6	3	2	2	1

Notes: 24 inches nominal for joint cutbacks up to 16 inches (400 mm); maximum 12 inches is recommended for FBE coated pipes with cutbacks of 6 inches (150 mm).

W= sleeve width

AT-DIRAX-REV-5-0309

Berry Plastics warrants that the product conforms to its chemical and physical description and is appropriate for the use stated on the technical data sheet when used in compliance with Berry Plastics written instructions. Since many installation factors are beyond the control of Berry Plastics, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection herewith. Berry Plastics liability is stated in the standard terms and conditions of sale. Berry Plastics makes no other warranty either expressed or implied. All information contained in this technical data sheet is to be used as a guide and is subject to change without notice. This technical data sheet supersedes all previous data sheets on this product.



CORROSION PROTECTION GROUP
www.berrycpg.com

Local Distributor / Representative:

For contact details of local Distributors / Representatives
Please visit www.berrycpg.com.

Headquarters : Berry Plastics Tapes & Coatings Division, Franklin MA, USA

Franklin, MA, USA
Tel: +1 508 918 1714
US Toll Free: +1 800 248 0149
Fax: +1 508 918 1910
CPG@berrypastics.com

Houston, TX, USA
Tel: +1 713 676 0085
US Toll Free: 01 888 676 7202
Fax: +1 713 676 0086
CPGH@berrypastics.com

Tijuana, Mexico
Tel USA +1 858 633 9797
Fax US: +1 858 633 9740
Tel Mexico: +52 664 647 4397
Fax Mexico: +52 664 647 4370
CPGTJ@berrypastics.com

Aarschot, Belgium
Tel: +32 16 55 36 00
Fax: +32 16 55 36 74
CPGE@berrypastics.com

Baroda, India
Tel: +91 2667 264721
Fax: +91 2667 264724
CPGIN@berrypastics.com