



Features/Applications

GREMARK® GR TT6100 and GR TT6900 are thermal transfert ribbons specially developed for the GREMARK® products family.

GREMARK® GR-TT6100 offers very good print permanence. It is recommended for use in the electrical and railway industries.

Preferred Printer/Tubing combination

Thermal transfert printer:

A4+M (one side), XD4M (double side).

Heat-shrink tubing:

GREMTUBE® PG61, PG61 3X, GREMARK® GMEC2, GMEC3, PG55Z.

Dimensions

Standard width (mm)	Standrad Colours	Ink Side	Core - Inside Diameter (mm)	Standard Length (m/ribbon)
GREMARK® GR-TT6100				
20, 40, 80 or 110	Black, white	Ink side out	25,4	300

GREMARK® GR-TT6900 offers very good print permanence and high chemical resistance (diesel, fuel and oil). It is recommended for railway industry.

Preferred Printer/Tubing combination

Thermal transfert printer:

A4+M (one side), XD4M (double side).

Heat-shrink tubing:

GREMARK® GMG2, GMG3, PGDR135, GMDR.

Dimensions

Standard width (mm)	Standrad Colour	Ink Side	Core - Inside Diameter (mm)	Standard Length (m/ribbon)
GREMARK® GR-TT6900				
20, 40, 80 or 110	Black	Ink side out	25,4	300

Recommended storage conditions: Keep in cool, dry, ventilated storage (maximum temperature of 35°C) and in closed containers.

Please contact our technical support to choose the ribbon linked to the application(tubing/sleeve/printer).



We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. Gremco shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.