



Optical Splice Closure - FK-CEO-3T-36F

Product Type Optical Splice Closure

Product Family FBS - Furukawa Broadband System

Warranty 12 months

Description

The Optical Splice Closure FK-CEO-3T has the purpose to accommodate and to protect the optical splices between the feeder and the branching cables from the distribution network. It supports up to 36 fibers, settled in splice trays with capacity of 12 splices each. It accepts main cables with maximum diameter of 15 mm and up to 3 branching cables with maximum diameters of 12 mm.

Application

It allows aerial installation in pole/wall or in strands (supports included). It has high resistance to corrosion and aging, besides UV protection.

Advantage

Closing and box sealing using O'ring;
It allows locking with padlock;
Loose tube storage tray included;
Accommodation system: separated areas for storing, forwarding, protection and transport of the fibers.

Physical Characteristics

Size	288 (height) x 178 (diameter) mm
Body material	PP + FG
Color	Black
Weight	1.75 kg
Entry cable diameter	2 cables from 8 to 15 mm
Derivation cable diameter	3 cables from 8 to 12 mm
Operation Temperature	-40 to 65 °C
Protection Rating	IP 67

Standards and Certifications Anatel 03261-16-00256

Compatibility

Identification 35520053 - FK-CEO-3T-36F (AERIAL/UNDERGROUND OPTICAL SPLICE CLOSURE)

Included Accessories

3 Splice Trays with capacity for 12 splices each one;
1 Loose tube storage tray;
1 kit for the main port (heat-shrinkable sleeve, cable separation clip, aluminum sheet and tissues);
1 kit for each branching port
1 Pole/Wall Mounting Kit
1 Strand Mounting Kit