



### Features/Applications

GREMTUBE® GFEP RC is a highly flame retardant, modified fluorinated ethylene propylene (FEP) heat shrink tubing. GREMTUBE® GFEP RC offers excellent temperature performances, an excellent resistance to chemicals, a low coefficient of friction and an outstanding mechanical resistance. Gremtube GFEP RC is suitable for protecting printing rolls and eliminating the accumulation of sticky material.

### Various

Standard colour: Clear.

### Dimensions



Reference <i>GREMTUBE® GFEP RC</i>	As supplied (mm) Inside Diameter Mini. (D)	To cover roll diameter		Standard Length (m)
		Min.	Max.	
1/2	12.70	11,10	14,00	On request
5/8	15.88	13,70	17,80	
3/4	19.05	16,20	20,30	
7/8	22.23	19,30	24,10	
1	25.40	22,30	27,90	
1-1/4	31.75	25,40	33,00	
1-1/2	38.10	35,60	43,20	
2	50.80	45,70	53,30	
2-1/2	63.50	55,90	66,00	
3	76.20	68,60	78,70	
3-1/2	88.90	81,30	91,40	
4	101.60	88,90	106,70	
5	127.00	111,80	132,10	
6	152.40	137,20	157,50	
7	177.80	162,60	182,90	
8	203.20	190,50	208,30	
9	228.60	215,90	233,70	
10-1/2	266.70	243,80	271,80	
12	304.80	284,50	310,00	

●Cut pieces available on request

### Property

Property	Values	Test Methods
Working temperature	-55°C to +204°C	-
Longitudinal change	±30 %	-
Flammability	Pass	UL94V0
Chemical resistance	Inert	-
Dielectric strength	>2000V/mm	-

Recommended storage conditions: Keep in cool, dry, ventilated storage (maximum temperature of 35°C) and in closed containers.



We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. Gremco shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.