



PRODUCT SPECIFICATIONS

TEK™ SERIES CONSTANT WATT HEATING CABLE

APPLICATION

TEK series resistance constant watt heating cables are used where circuit lengths exceed the limitations of parallel resistance heating cables. Circuit lengths up to 3,658 m can be energized from a single power supply point.

The series circuitry of TEK provides consistent watt-per-foot power output along the entire length of the cable.

TEK cables are certified for use in ordinary (nonclassified) areas and in potentially explosive atmospheres in accordance with the ATEX Directive and the IEC Ex Scheme.

RATINGS

Rated voltage ¹for operation up to 750 Vac
 Max. maintenance temperature ²..... 101°C ³
 Max. continuous exposure temperature
 Power-off250°C
 Minimum installation temperature.....-60°C
 Minimum bend radius
 @ -15°C22mm
 @ -60°C32 mm
 T-ratingT2 to T6 ⁴
 (using the principles of stabilised design or limiters)

STABILISED DESIGN . . .

The watt density limitation for TEK cables is directly related to the desired maintain temperature. Thermon is able to ensure the T-rating based on a stabilised design that enables series constant watt heating cables to operate in hazardous areas without the use of limiter thermostats.

Notes

1. Definition as stated in IEC 60079-30-1. Specific voltage depends on circuit length and design conditions.
2. Watt density limitations are correlated to maintain temperatures.
3. Higher maintenance temperatures may be possible; contact Thermon for design assistance.
4. Heating cable output and T-rating are dependent upon supply voltage, cable resistance, temperature conditions as well as additional variables. These may be determined using CompuTrace® Electric Heat Tracing Design Software or by contacting Thermon design assistance..



CONSTRUCTION

- 1 Heating Conductors (2 or 3)
- 2 Fluoropolymer Dielectric Insulation
- 3 Fluoropolymer Pairing Jacket
- 4 Nickel-Plated Copper Braid (BN)
- 5 Fluoropolymer overjacket provides additional protection to cable and braid where exposure to chemicals or corrosives is expected.

BASIC ACCESSORIES

Power Connection: All TEK cables require a Terminator or cold lead transition for connection to power. Refer to the back of this specification sheet for details.

End-of-Circuit Termination: An end-of-circuit termination must also be used with TEK cables. This termination, detailed on the back of this specification sheet.

THERMON The Heat Tracing Specialists®

ISO 9001
REGISTERED

European Headquarters: Boezemweg 25 • PO Box 205 • 2640 AE Pijnacker • The Netherlands • Phone: +31 (0) 15-36 15 37
 Corporate Headquarters: 100 Thermon Dr • PO Box 609 San Marcos, TX 78667-0609 • Phone: 512-396-5801 • 1-800-820-4328
 For the Thermon office nearest you visit us at . . . www.thermon.com

Form TEP0021U-0913 • © Thermon Manufacturing Co. • Printed in U.S.A. • Information subject to change.



AVAILABLE CABLES

Catalog Number		Resistance per Conductor at 20°C Ohms/m	Conductor Size (mm)²
2 Conductor	3 Conductor		
TEK 2C40	TEK 3C40	0.01492	1.3
TEK 2C50	TEK 3C50	0.009449	2.1
TEK 2C60	TEK 3C60	0.005945	3.3
TEK 2C70	TEK 3C70	0.003478	5.3

CIRCUIT BREAKER SIZING AND TYPE¹

Circuit breaker sizing and earth-fault protection should be based on applicable local codes. For information on design and performance, contact Thermon.

Earth-fault protection of equipment should be provided for each branch circuit supplying electric heating equipment.

TERMINATIONS AND SPLICES

Prior to connection to power, TEK heating cables should be terminated using the Terminator ZP-M or with a certified nonheating “cold lead” and a “hot-end” termination. To facilitate ease of installation, in-line splices may also be required. These connections/terminations are available as factory fabricated assemblies or as field fabricated kits.

Power Connection: Provides fluoropolymer insulated nickel-plated stranded copper cold leads and ground wire extension plus required splices, insulating tape and sealant. A flexible stainless steel conduit with a 3/4” fitting protects the leads. The number and size of the cold leads is based on the TEK heater type. Exposure temperatures up to 190°C.

End Termination: The hot end (opposite end from power) utilizes an under insulation stainless steel fitting that houses the lug, insulating tape, sealant and grounding lug. The size and style of the termination is based on the number and size of conductors. Exposure temperatures up to 190°C.

In-Line Splices: To facilitate the installation of the cable, an under insulation splice may be required. The splice utilizes a stainless steel housing (sized for the conductor type and number), splices, grounding lugs, insulating tape and sealant. Exposure temperatures up to 190°C.



CETK: Field fabricated cold-end termination kit.



HETK: Field fabricated hot-end termination kit.



HSTK: Field fabricated splice termination kit.

CERTIFICATIONS/APPROVALS

II 2 G Ex eb IIC T260°C (T2) to T6
II 2 D Ex tb IIIC T260°C to T85°C FM 11ATEX0050

International Electrotechnical Commission
IEC Certification Scheme for Explosive Atmospheres
CCVE 11.0002

Factory Mutual Research
Ordinary and Hazardous (Classified) Locations

Underwriters Laboratories Inc.
Hazardous (Classified) Locations



Terminator ZP-M: Designed to fabricate power connections, in-line splice connections or for making end terminations. Electrical connections are made in terminal blocks utilizing nickel-plated copper terminals to ensure corrosion-free electrical integrity. No cold leads are required. Exposure temperatures up to 250°C.