

ELEKTRA Installation Accessories

Installation Tapes TME

TME 10 (10 m), TME 15 (15 m), TME 25 (25 m)

Thickness: ~ 0.8mm, Substance: aluminium

Installation Tape TMS

TMS 10 (10 m)

Thickness: ~ 1.0 mm, Substance: zinc-coated steel

Roof runner installation tape (0.5 m)

Width: 25 mm, Substance: aluminium (0.8 mm)
with special self-adhesive tape suitable for metal and PVC

Gutter spacing wire with clips (20 m)

The distance between the holders along the wire: 40 cm
Substance: stainless steel and all weather resistant polymer

Downpipe spacing wire with clips (20 m)

The distance between the holders along the wire: 40 cm
Substance: stainless steel and all weather resistant polymer

Roof runner installation band (1 m)

Substance: all weather resistant polymer

Gutter holder (25 pieces)

Substance: all weather resistant polymer

Downpipe spacing clip (25 pieces)

Substance: all weather resistant polymer

Roof edge installation holder

(25 pieces) Substance: ZnTi or Cu

Flexible cable support (25 x 250mm, 2 pieces)

Substance: stainless steel

Downpipe spacing wire support bar

(Ø 6 x 325mm)

Substance: stainless steel



Underfloor heating installation monitor

Monitoring device for detection of damages occurring during heating mats and cables' installation



Self-adhesive installation tape

(5, 10 or 20 m)



Self-adhesive aluminium foil

(5 m, 10 m, 25 m, 45 m) Width: 50 mm



Tape-PRO

Self-adhesive aluminium foil of increased mechanical durability
(100 m) Width: 50 mm

